## **CLAIMS**

None of the claims has been amended. The claims are reproduced here for the Examiner's convenience.

1. (Previously Presented) A method for receiving and storing voice mail messages, the method comprising:

receiving, at a first server, an incoming call;

determining whether the call is to be transferred to voice mail; and responsive to determining that the call is to be transferred to voice mail:

determining the call's voice mail extension;

determining a second server, the second server being the voice mail extension's home server;

determining whether the second server is a remote server; and responsive to determining that the second server is a remote server:

determining whether the second server is available; and responsive to determining that the second server is not available, storing the voice mail message in the first server.

2. (Original) The method of claim 1, further comprising;

responsive to determining that the call is not to be transferred to voice mail, handling the call normally.

3. (Original) The method of claim 1, further comprising:

responsive to determining that the second server is not a remote server, storing the voice mail message in the first server.

- 4. (Original) The method of claim 1, further comprising:
  responsive to determining that the second server is available, sending the voice mail message to the second server.
- 5. (Previously Presented) A method for distributing voice mail messages, the method comprising:

determining, at a first server, whether a second server is available; and responsive to determining that the second server is available:

retrieving a voice mail message from the first server; and sending the voice mail message to the second server.

- 6. (Previously Presented) The method of claim 5, further comprising: querying a configuration module for a location of the second server.
- 7. (Previously Presented) The method of claim 5, further comprising:
  responsive to determining that the second server is available:
  receiving, by the second server, the voice mail message; and
  storing, by the second server, the voice mail message.
- 8. (Previously Presented) An apparatus for receiving, storing, and distributing voice mail messages, the apparatus comprising:
  - a call status module, configured to determine whether a call should be transferred to voice mail;
  - a call transfer module, configured to determine a call's voice mail extension and a server on which the voice mail extension resides, wherein the server is one of a plurality

of servers, and wherein voice mail extensions reside on each server of the plurality of servers; and

a voice mail migration module, configured to send a voice mail message to a remote server.

## 9. (Original) The apparatus of claim 8, wherein:

the call transfer module is further configured to determine whether the server on which the voice mail extension resides is a remote server.

- 10. (Original) The apparatus of claim 8, further comprising:
  - a storage interface module, configured to allow modules to store and retrieve data.
- 11. (Original) The apparatus of claim 8, further comprising:

an audio encoding/decoding module, configured to convert audio voice mail messages to a data format suitable for storage and to convert voice mail messages from this storage data format to an audio format.

## 12. (Original) The apparatus of claim 8, further comprising:

a telephony application programming interface module, configured to allow modules access to data on a switch.

- 13. (Original) The apparatus of claim 8, further comprising:
  - a configuration module, configured to provide information about remote servers.
- 14. (Original) The apparatus of claim 8, further comprising:

an extension library module, configured to provide common functions that are used by modules.

- 15. (Previously Presented) A system for receiving, storing, and distributing voice mail messages, the system comprising:
  - a first apparatus for receiving, storing, and distributing voice mail messages, the first apparatus comprising:
    - a first call status module, configured to determine whether a first call should be transferred to voice mail;
    - a first call transfer module, configured to determine a first call's voice mail
      extension and a first server on which the first voice mail extension resides,
      wherein the first server is one of a plurality of servers, and wherein voice
      mail extensions reside on each server of the plurality of servers; and
      a first voice mail migration module, configured to send a first voice mail message
  - a second apparatus for receiving, storing, and distributing voice mail messages, the second apparatus comprising:

to a first remote server; and

- a second call status module, configured to determine whether a second call should be transferred to voice mail;
- a second call transfer module, configured to determine a second call's voice mail extension and a second server on which the second voice mail extension resides, wherein the second server is one of a plurality of servers, and wherein voice mail extensions reside on each server of the plurality of servers; and
- a second voice mail migration module, configured to send a second voice mail message to a second remote server;

wherein the first apparatus and the second apparatus are coupled to each other.	